



art. 1810 DIANA HP/QP

Mod	QP	Installation	Leaning recessed fixture for false ceilings panels with visible structure mm 15/24
Material	Steel body, painted with white epoxypolyester powders anti-yellowing, with phosphate and degreasing pretreatment	Insulation class	Class I
Protection index	IP40	Impact degree	IK07
Color rendering index (CRI)	> 80	Ambient temperature (Ta)	-25 / +45 °C
Optics	Microprismatic polycarbonate diffuser	UGR	< 19
Power supply	230V 50/60Hz	Incandescent wire resistance	850°
Trademarks and certifications	CE / UNI EN 60598-1:2015	Warranty	5 years
Luminous flux maintenance	L80-B50 (90.000h) - L70-B50 (140.000h)	Photobiological safety class	IEC 62471: Rischio esente
Beam angle	150°		

CODE

Art.	+	Mod.	+	°K	+	W-tot.	+	Opt.
1810		QP		03 = 3000°K		48		EL = standard
				04 = 4000°K		72		LM = 1-10 V
				05 = 5000°K				LD = dali
				65 = 6500°K				E1 = em-1h
								E3 = em-3h

W-tot	°K	Lm [Tc=25°]	Lm [Output]	A	B	C	Kg	Lamp	Sost.
48	4000	8084	5683	595	60	595	4,5	6x32 led	4x24W fluo
72	4000	11099	7802	595	60	595	4,5	6x32 led	4x40W FL-C

*The flux may vary from -5/+5% compared to the real.

• 3000K = -5,15% lm • 4000K = standard • 5000K = +1,46% lm • 6500K = 0% lm

